

**ASSAM PROJECT
ON
FOREST AND BIO-DIVERSITY CONSERVATION
CONSTRUCTION OF NEW RESIDENTIAL QUARTERS
– AT REHABARI, GUWAHATI - 781 008.**

BILL OF QUANTITIES OF ROAD SIDE DRAIN

Sl. No.	Specification of item of works	Unit	Quantities	Rate in Rs.		Amount (in Rs.)
				(in Figures)	(in Words)	
	EARTHWORK IN EXCAVATION					
1	Earthwork in excavation for foundation trenches of walls, retaining walls, footings of column, steps, septic tank etc. including refilling (return filling) the quantity as necessary after completion of work, breaking clods in return filling, dressing, watering and ramming etc. and removal of surplus earth with all lead and lifts as directed and specified in the following classification of soils including bailing out water where necessary as directed and specified. (A) Up to a depth of 2.00m below the existing ground level. (a) In ordinary soil	Cu.M.	88.00			

Sl. No.	Specification of item of works	Unit	Quantities	Rate in Rs.		Amount (in Rs.)
				(in Figures)	(in Words)	
2	PLAIN CEMENT CONCRETE WORKS Plain cement concrete works with coarse aggregate of sizes 13mm to 32mm in foundation bed for footing steps, walls, brick works etc. as directed and specified including dewatering if necessary, and curing complete (shuttering where necessary shall be measured and paid separately). (a) In prop 1cement: 3 sand :6 coarse aggregate by volume	Cu.M.	10.00			
3	MASONRY WORKS Providing soling in foundation and under floor with stone/ best quality picked jhama brick, sand packed and laid to level and in panel after preparing the subgrade as directed including all labour and materials and if necessary dewatering, complete. (a).Brick on flat soling.	Sq.M.	96.00			
4	IN SUB-STRUCTURE. Brick work in cement mortar with 1st class brick including racking out joints and dewatering if necessary, and curing complete as directed (I) In Sub-structure up to plinth level. (a). In proportion 1:4.	Cu.M.	36.00			

Sl. No.	Specification of item of works	Unit	Quantities	Rate in Rs.		Amount (in Rs.)
				(in Figures)	(in Words)	
5	CEMENT PLASTERING 15 mm thick Cement plaster in single coat on rough side of single or half brick wall for interior plastering up to 1st floor level including arises, internal rounded angles, not exceeding 80mm girth and finished even and smooth including curing complete as directed. A) On rough side (a). In cement mortar 1:4	Sq.M.	216.00			
6	Neat Cement Punning	Sq.M.	216.00			
TOTAL = Rs.						

Rupees

Signature of the Contractor :

Date & Seal :